

4000/4200 PRE-DELIVERY INSPECTION

DATE _____

DEALERSHIP _____

MODEL SIZE _____

SERIAL # _____



Wheel's and Axles

Ensure that the bolts on the axles are tight and located properly	
Wheel torque should be at 160 ft/lbs for all tires	
Tire pressure should be at 36 PSI on the 36-42 MF tires (12.5L x 15FI 8ply)	
Tire pressure should be at 60 PSI on the 28-32 MF tires (9.5L x 15FI 8 ply)	
Tire pressure should be at 60 PSI on the 48-52 MF tires (9.5L x 15FI 8 ply)	
Tire pressure should be at 60 PSI on all wing tires (9.5L x 15FI 8 ply)	
Ensure that all the axle end caps and hubs are greased	

Hydraulics

Check

Ensure that there are no hydraulic leaks		
Ensure that the wings are all the way down before main frame begins to lower. If the main frame lowers before this the sequence valve needs to be set.		

Frame and Hitch

Check

All bolts are tight on the hitch		
All bolts are tight on the mainframe		
Cotter pins are installed on the cylinders and the wing pins		
Safety lights function properly		
Safety chain and rear jack are installed		

1-1/8" socket
1-1/16" deep socket
Tape Measure

3/4" flat wrench
7/8" deep socket
Tire Pressure Guage

Suggested Completion Time = 30min.

Actual Time

Signature: _____

Packer Coils

All set screws are in place and tight with retaining straps on the collars	
All bolts are tight on the packer bearings and arms	
Proper coil configuration used (quantity is listed for each size)	
All packer bearings have been greased.	

COIL CONFIGURATIONS

<p>24'</p> <p>36" Right 2 pcs 48" Right 2 pcs 48" Left 2 pcs 60" Left 1 pc</p> <p>28'</p> <p>36" Right 2 pcs 48" Right 2 pcs 60" Left 3 pcs</p> <p>32'</p> <p>48" Right 2 pcs 60" Left 3 pcs 60" Right 2 pcs</p> <p>36'</p> <p>36" Right 2 pcs 48" Right 2 pcs 48" Left 2 pcs 60" Left 3 pcs</p> <p>40'</p> <p>48" Right 4 pcs 60" Left 5 pcs</p> <p>42'</p> <p>48" Right 2 pcs 60" Right 2 pcs 60" Left 5 pcs</p>	<p>48'</p> <p>36" Right 2 pcs 48" Left 2 pcs 60" Right 4 pcs 60" Left 3 pcs</p> <p>50'</p> <p>48" Right 2 pcs 48" Left 2 pcs 60" Left 3 pcs 60" Right 4 pcs</p> <p>52'</p> <p>48" Right 2 pcs 60" Right 4 pcs 60" Left 5 pcs</p> <p>56'</p> <p>36" Right 2 pcs 48" Right 2 pcs 48" Left 2 pcs 60" Left 4 pcs 60" Right 3 pcs</p> <p>58'</p> <p>48" Right 4 pcs 48" Left 2 pcs 60" Right 3 pcs 60" Left 4 pcs</p> <p>60'</p> <p>48" Right 2 pcs 48" Left 2 pcs 60" Right 5 pcs 60" Left 4 pcs</p>
---	--

Suggested Completion Time = 10 min.

Signature: _____

Actual Time

Final Inspection

	<i>Check</i>
Wash off all road salt and debris.	
Repair any paint chips or defaults.	
Go through operator's manual with customer.	
Make sure hazard lights are fuctional.	

Suggested Completion Time = 15 min.

Signature: _____

Actual time